



搓牙機

Specifications of Thread Rolling Machines

機 型 Model No.	最大 可製 外徑 Max Cut-off Dia. (mm)	最大 可製 螺紋 長度 Max Cut- off Length (mm)	主馬力 Main Motor (HP)	每分鐘 生產量 Max Output (pc/min)	牙板高 Height of Rolling Die (mm)	牙板尺寸 Rolling Die Dimensions L * T (mm)	機械淨重 (噸) Net Weight (Ton)
TR6R-S	6	50	7.5HP	280	56	90 x 25 105 x 25	1.4
TR6R-L	6	75	7.5HP	280	80	90 x 25 105 x 25	1.4
TR8R-S	8	75	10HP	220	80	108 x 25 127 x 25	2.4
TR8R-L	8	100	10HP	180	105	108 x 25 127 x 25	2.4
TR5/16-S	8	100	15HP	150	110	127 x 25 140 x 25	3
TR5/16-L	8	150	15HP	120	160	127 x 25 140 x 25	3.2
TR5/16-LL	8	150	20HP	120	210	127 x 25 140 x 25	3.8
TR3/8-S	10	100	25HP	140	110	150 x 25 165 x 25	4
TR3/8-L	10	150	25HP	130	160	150 x 25 165 x 25	4.4
TR3/8-LL	10	150	25HP	120	210	150 x 25 165 x 25	5
TR1/2-S	14	150	40HP	100	160	190 x 35 215 x 35	7
TR1/2-L	14	200	40HP	100	210	190 x 35 215 x 35	7
TR1/2-LL	14	300	40HP	60	310	190 x 35 215 x 35	9
TR3/4-S	20	150	50HP	70	160	230 x 38 265 x 38	8.5
TR3/4-L	20	200	50HP	70	210	230 x 38 265 x 38	9
TR7/8-S	24	200	60HP	60	210	290 x 45 330 x 45	14
TR7/8-L	24	250	60HP	60	260	290 x 45 330 x 45	15
TR1-1/8"-S	27	200	75HP	55	210	400 x 50 450 x 50	20
TR1-1/8"-L	27	300	75HP	50	310	400 x 50 450 x 50	21

(1) 本公司保有規格修改之權利，規格修改時，不另行通知。

Modification subjected to change without any prior notice.

(2) 本公司之機台設計部份，可依客戶要求做適當變更。

The design of unit can be modified upon request.